



AU9224886

(12) PATENT ABRIDGMENT (11) Document No. AU-B-24895/92
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 659209

- (54) Title
REEL MECHANISMS FOR GAMING MACHINES
- (51)^a International Patent Classification(s)
G07F 017/34
- (21) Application No. : 24895/92 (22) Application Date : 01.09.92
- (87) PCT Publication Number : WO93/05484
- (30) Priority Data
- | | | |
|-------------|-----------|-------------------|
| (31) Number | (32) Date | (33) Country |
| 9118773 | 02.09.91 | GB UNITED KINGDOM |
| 9125844 | 04.12.91 | GB UNITED KINGDOM |
- (43) Publication Date : 05.04.93
- (44) Publication Date of Accepted Application : 11.05.95
- (71) Applicant(s)
STARPOINT ELECTRICS LIMITED
- (72) Inventor(s)
ROBERT ALAN HOLMES
- (74) Attorney or Agent
PHILLIPS ORMONDE & FITZPATRICK, 387 Collins Street, MELBOURNE VIC 3000
- (56) Prior Art Documents
GB 2182478
GB 2160345
GB 2156565

- (57) Claim
1. A reel mechanism including a support which carries a motor, a reel, a lamp and an optical device;

the motor carrying the reel, the reel including both a reel strip provided with symbols to be illuminated by the lamp as well as a reel support provided with a tab to be sensed by the optical device, and the lamp being adjustably movable relatively to the support;

wherein the optical device is also adjustably movable relatively to the support.

OPI DATE 05/04/93 APPLN. ID 24895/92
AOJP DATE 10/06/93 PCT NUMBER PCT/GB92/01597



AL9224893


Y (PCT)

(51) International Patent Classification S: G07F 17/34		A1	(11) International Publication Number: WO 93/05484
			(43) International Publication Date: 18 March 1993 (18.03.93)
(21) International Application Number: PCT/GB92/01597		(81) Designated States: AU, GB, JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, SE).	
(22) International Filing Date: 1 September 1992 (01.09.92)			
(30) Priority data: 9118773.2 2 September 1991 (02.09.91) GB 9125844.2 4 December 1991 (04.12.91) GB		Published With international search report.	
(71) Applicant (for all designated States except US): STAR-POINT ELECTRICS LIMITED (GB/GB); 188 Garth Road, Morden, Surrey SM4 4NH (GB).		659209	
(72) Inventor; and (75) Inventor/Applicant (for US only): HOLMES, Robert, Alan [GB/GB]; 18 Mandeville Drive, Ditton Hill, Surrey KT6 5DT (GB).			
(74) Agent: GILL JENNINGS & EVERY; 53/64 Chancery Lane, London WC2A 1HN (GB).			

(54) Title: REEL MECHANISMS FOR GAMING MACHINES

(57) Abstract

A reel mechanism (10) comprising a support (12) which carries a motor (14), a reel (16), a lamp (26) and an optical device (28); the motor carrying the reel, the reel including both a reel strip (18) provided with symbols (20) to be illuminated by the lamp as well as a reel support (22) provided with a tab (24) to be sensed by the optical device, and the lamp being adjustably movable relatively to the support; characterised in that the optical device (28), and preferably the motor, are also adjustably movable in unison with the lamp (26) relatively to the support (12).



IGT1008556

Starpoint Electrics Limited

REEL MECHANISMS FOR GAMING MACHINES

5 The present invention relates to the construction of reel mechanisms for gaming machines which are sometimes referred to as fruit machines or amusement machines.

It is well known that gaming machines can include adjacent reel mechanisms each comprising a reel marked
10 around its circumferential surface with symbols such as fruit. In operation, the reels are caused to spin about a common axis by pulling a handle or pressing a button. When the reels come to a standstill, the positions of the symbols on the different reels in relation to one or more
15 predetermined lines decide whether or not a player has won.

Each predetermined line may take the form of a row of windows or other openings in the gaming machine.

Each reel is typically formed from a reel strip and a reel support.

20 The reel strip is usually formed of a plastics material. Typically it is a translucent plastics material with a predetermined number of the symbols printed or otherwise provided thereon. The reel strip is usually illuminated from behind, with a respective lamp being
25 provided for the or each of the openings associated with the reel strip.

For each of the reel strips, there may be an array of for example three of the lamps associated with opening(s) through which an adjacent three of the symbols can be seen.

30 The reel support is usually also formed of a plastics material. It may include a pair of co-axial rings joined by circumferentially spaced cross-pieces to define a skeletal drum around which the reel strip is to be wrapped. Alternatively, it may include a single ring formed with an
35 annular slot into which an edge of the reel strip is to be inserted. The or one of the rings may have several spokes extending radially inwardly therefrom to a central drive

connector, for releasable connection with a rotatable spindle of a motor such as a stepper motor.

The motor may be adjustably carried by a support which is to be mounted on support structure within the gaming machine, the support also being used to carry an optical device which is to be connected to electrical circuitry within the gaming machine.

Each of the optical devices may include an emitter and an associated sensor located in positions such that a part of the associated reel passes therabetween upon each revolution of the reel. For example, a projecting part of a reel in the form of a tab may be used to break a beam of light or infra-red radiation directed from an emitter to a sensor. The breaking of the beam may be detected by the electrical circuitry to provide information as to the angular position of the reel relatively to the optical device and/or the number of times that the reel has been spun.

It is important operationally that when the tab is positioned centrally between the emitter and the sensor of the optical device, or at a known position relatively thereto, one of the symbols on the reel strip is positioned between a lamp and an opening associated therewith, whereby said symbol is both fully and clearly visible.

Hitherto, in order to achieve this relationship it has been necessary to make several checks and adjust as appropriate.

For each of the reel strips, the lamp(s) need to be in the correct position relatively to the associated opening(s). The relationship of the opening(s) to the support structure is known for any given gaming machine and is commonly different for different gaming machines. It is thus necessary to be able to adjust the positions of the lamp(s) and this capability is usually provided by mounting the lamp(s) for angular adjustment on the associated support. There can be a releasable pin-and-slot type connection, between a housing for the lamp(s) and the

support, enabling the lamp(s) to be moved relatively to the associated opening(s). There can also be calibrations on the support to facilitate setting of the lamp(s) in a predetermined position correct for the given gaming machine.

It is also necessary for the symbol(s) to be in the correct position relatively to the associated tab. As the relationship of the opening(s) to the support structure is commonly different for different gaming machines, and the optical device has always hitherto been in a fixed position on the support, it has been necessary to be able to adjust the position of the tab relatively to the symbol(s). This capability has usually been provided by mounting the tab for angular adjustment around the periphery of the or one of the rings forming part of the reel support. When the symbol(s) are in the correct position relatively to the associated opening(s), the angular position of the tab on the reel support is adjusted to locate the tab centrally between the emitter and the sensor of the fixed optical device, or less commonly at a known position relatively thereto.

In practice, because the reel may not be in a position determined by the electrical circuitry, it may be necessary after energisation of the motor to adjust the position of the motor relatively to the support, and this is again usually achieved by a releasable pin-and-slot type connection, between a housing for the motor and the support.

An aim of the present invention has been to simplify the above-described adjustment procedures, especially when transferring a reel mechanism from one gaming machine to another gaming machine of different constructional characteristics.

According to the present invention, a reel mechanism comprises a support which carries a motor, a reel, a lamp and an optical device;



the motor carrying the reel, the reel including both a reel strip provided with symbols to be illuminated by the lamp as well as a reel support provided with a tab to be sensed by the optical device, and the lamp being adjustably movable relatively to the support;

~~characterised in that~~ ^{wherein} the optical device is also adjustably movable relatively to the support.

It will be appreciated that in the present invention there is no need to provide for "adjustment" of the position of the tab relatively to the reel strip, even for different gaming machines having different constructional characteristics, because it is merely necessary to provide for predetermined "location" of the tab relatively to the reel strip.

This can be easily achieved in a manner known per se. The reel strip may be provided with identification such as a printed line, perforation or peripheral notch to be aligned with a complementary marking, peg or rib provided on the reel support in a known position relatively to the tab provided on the reel support. As the tab need not be adjustable it can be moulded or fixedly secured to the reel support.

Preferably, the centre line between an emitter and a sensor of the optical device is in radial alignment with the centre line of a filament of the lamp.

Also preferably, the lamp is carried by a lamp housing and the optical device is also carried by the lamp housing to be movable in unison therewith. There may be a snap connection between the optical device and the lamp housing. There may be an array of three of the lamps carried by a common lamp housing formed of a plastics material. The optical device may be of generally conventional construction. It may thus include its own electrical circuitry or alternatively be connectable to electrical circuitry by appropriate releasable or non-releasable connectors.



In a modification, the need to effect realignment of the motor is avoided by arranging for the motor to be adjustably movable relatively to the support in unison with the adjustment of the lamp(s) and the optical device.

5 In particular, instead of a motor housing being carried by the support, the lamp housing may carry each of the motor, the lamp(s) and the optical device. At a sub-assembly stage in production the motor is powered-up and set in a desired position on the lamp housing and need
10 never be adjusted again. The sub-assembly, including the lamp housing, the motor, the lamp(s) and the optical device, may be clipped onto the support to be angularly adjustable relatively thereto.

Two reel mechanisms, in accordance with the present
15 invention, will now be described in more detail, by way of example only, with reference to the accompanying drawings, in which:-

Figure 1 is a partly fragmented schematic side view of one of the reel mechanisms;

20 Figure 2 is a partly fragmented schematic cross-sectional view of the reel mechanism of Figure 1 taken along the broken line II-II but repositioned such that the tab is located centrally of the optical device; and

Figures 3 and 4 are similar to Figures 1 and 2,
25 respectively, but show the other of the reel mechanisms.

As shown in Figures 1 and 2, a reel mechanism 10 in accordance with the present invention comprises a support 12, a motor 14 carried by the support 12, a reel 16 carried by the motor 14 and including both a reel strip 18 provided
30 with symbols 20 as well as a reel support 22 provided with a tab 24, a lamp 26 adjustably movable relatively to the support 12, and an optical device 28 also adjustably movable relatively to the support 12.

Many of the above-listed components are of generally
35 conventional construction and thus need not be described in detail.

Thus, the support 12 may be a plastics lattice-like frame including a pair of legs 30 to be secured by screws to support structure (not shown) within a gaming machine. The motor 14 may be adjustable angularly relatively to the support 12 by a known pin-and-slot type connection indicated at 32. The reel strip 18, when wrapped into cylindrical shape, may have one edge of its translucent plastics material located within and supported by an annular slot 34 provided by the reel support 22. The angular position of the reel strip 18 in the annular slot 34 may be determined by providing said edge of the reel strip 18 with a notch (not shown) which locates as a push-fit on a rib protruding from the base of the annular slot 34. There may be three of the lamps 26 in a common lamp housing 36 which is angularly adjustable relatively to the support 12 by another pin-and-slot type connection with calibrations indicated at 38. The optical device 28 may include an infra-red emitter 40 and a phototransistor sensor 42 located on a plastics housing 44 which is connectable to electrical circuitry (not shown) or indeed contains its own electrical circuitry.

Particular features of this embodiment of the present invention are:-

- a) the tab 24 is moulded as a blade on, or otherwise fixedly secured to, one of three spokes 46 of the reel support 22; and
- b) the optical device 28 is fixedly secured to the common lamp housing 36 for movement in unison therewith.

There may be a snap connection between the housing 44 of the optical device and a bracket 48 extending from the common lamp housing.

When transferring the reel mechanism 10 from one gaming machine to another, in which there is a different relationship (physical separation/orientation) between its support structure and its windows through which the illuminated symbols 20 are visible, it is merely necessary to adjust the position of the common lamp housing 36,

thereby at the same time adjusting the position of the optical device 28, and then realign the motor 14 to said adjusted position.

In this embodiment, the motor 14 includes an apertured
5 flange 50 secured by a screw 52 to a motor housing 54
formed of a plastics material with a cylindrical bearing
portion 56 and a plurality of spaced-apart resilient clips
58. There may be three of the clips 58 on the motor
housing 54 for snap assembly in respective arcuate slots
10 (not shown) in the support 12 when the bearing portion 56
is received in a circular opening 60 in the support 12.
The motor housing 54 is engaged by a screw 62 of which only
its shank can extend through a circumferentially extending
slot in the support 12, with the screw 62 and its
15 associated slot constituting the pin-and-slot type
connection indicated at 32.

The need to realign the motor is avoided by the
embodiment of the present invention shown in Figures 3 and
4 in which components similar to those in the embodiment of
20 the present invention shown in Figures 1 and 2 have been
given similar reference numbers.

It can be seen that the lamp housing 36' carries each
of the motor 14', the lamp(s) 26' and the optical device
28'. The motor 14', the lamp(s) 26' and the optical device
25 28' are thus movable in unison with angular adjustment of
the lamp housing 36'. More particularly, the lamp housing
36' is integrally formed with the motor housing to include
the bearing portion 56' and the clips 58'. The support 12'
is engaged by a screw 66' of which only its shank can
30 extend through a circumferentially extending slot 68' in
the lamp housing 36', with the screw 66' and the slot 68'
constituting the pin-and-slot type connection with
calibrations indicated at 38'.

It should be appreciated that there is another pin-
35 and-slot type connection 70', allowing initial angular
adjustment of the motor 14' relatively to the lamp housing
36', the pin-and-slot type connection 70' being constituted

WO 93/05484

PCT/GB92/01597

8

by a screw 72' and a circumferentially extending slot in the lamp housing 36', which is partially obscured by one of the spokes 46'.

IGT1008564

The claims defining the invention are as follows:

1. A reel mechanism including a support which carries a motor, a reel, a lamp and an optical device;

the motor carrying the reel, the reel including both a reel strip provided with
5 symbols to be illuminated by the lamp as well as a reel support provided with a tab to be sensed by the optical device, and the lamp being adjustably movable relatively to the support;

wherein the optical device is also adjustably movable relatively to the support.

10 2. A reel mechanism according to claim 1, characterised in that the tab is secured to the reel support without being adjustable relatively thereto.

3. A reel mechanism according to claim 2, characterised in that the tab is integrally moulded in a plastics material on a spoke of the reel support.

4. A reel mechanism according to any preceding claim, characterised in that
15 the optical device is secured to a lamp housing for adjustment in unison therewith.

5. A reel mechanism according to claim 4, characterised in that the optical device is located in a housing which snap connects with a part of the lamp housing located radially inwardly of the lamp.

20 6. A reel mechanism according to any preceding claim, characterised in that the motor is adjustably movable relatively to the support in unison with the adjustment of the lamp and the optical device.

7. A reel mechanism according to claim 4 or claim 5, characterised in that the motor is adjustably movable relative to the support in unison with the adjustment
25 of the lamp and the optical device, and in that there is a pin-and-slot type connection between the support and the lamp housing.

8. A reel mechanism according to claim 7, characterised in that there is another pin-and-slot type connection between the motor and the lamp housing.

9. A reel mechanism according to any preceding claim, characterised in that
30 the optical device includes an infra-red emitter and a phototransistor sensor.

10. A reel mechanism according to any preceding claim, characterised in that the reel support includes a single ring formed with an annular slot into which an edge of the reel strip is to be inserted.

DATED: 27 February, 1995

PHILLIPS ORMONDE & FITZPATRICK

Attorneys for:


STARPOINT ELECTRICS LIMITED

David Fitzpatrick



Key Words: Cystic fibrosis; health care; patient participation; patient education; patient empowerment


Fig.1.



SUBSTITUTE SHEET

2/4

Fig. 2.




SUBSTITUTE SHEET

IGT1008568

3/4


Fig. 3.



SUBSTITUTE SHEET

4/4

Fig. 4.




SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 92/01597

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
Int.Cl. 5 G07F17/34		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl. 5	G07F	
Documentation Searched other than Minimum Documentation to the extent that such Documents are included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ^a	Citation of Document, ¹¹ with indications, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	GB,A,2 182 478 (STARPOINT ELECTRICS) 13 May 1987 see abstract; figures	1,6-8
A	GB,A,2 160 345 (STARPOINT ELECTRICS) 18 December 1985 see abstract; figures	1
A	EP,A,0 081 981 (UNIVERSAL) 22 June 1983 see abstract; figures 1,2 see page 3, line 27 - page 4, line 22	1-3,10
A	GB,A,2 156 565 (BARCREST) 9 October 1985	
<p>^a Special categories of cited documents: ¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"T" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combinations being obvious to a person skilled in the art</p> <p>"A" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search		Date of Mailing of this International Search Report
10 DECEMBER 1992		23 DEC 1992
International Searching Authority		Signature of Authorized Officer
EUROPEAN PATENT OFFICE		DAVID J.Y.H. 

Form PCT/ISA/210 (second sheet) (January 1993)

IGT1008571

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO. GB 9201597
SA 63949**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 10/12/92

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB-A-2182478	13-05-87	None	
GB-A-2160345	18-12-85	None	
EP-A-0081981	22-06-83	AU-B- 569410	28-01-88
		AU-A- 4628885	02-01-86
		US-A- 4765078	23-08-88
GB-A-2156565	09-10-85	None	

EP 0 208 198 1

For more details about this annex : see Official Journal of the European Patent Office, No. 12/93

IGT1008572